Application	on to construct driveway	y/access along tov	vn roads in Aztal	an Township: Date	
			Phone # City, State, Zip		
	riveway being applied			Field entrance (ag use only)	
	5 6 11			Tiera enviance (ag ase only)	
-	Location (side of road)		-	•••	
North	Soi	uth	East	West	
Distance 1	from driveway to neares	st intersecting road	d:		
Feet/miles	Direction Roa	nd Name			
Work bein	ng performed by				
ov Ch a.  b. c. d. e.  f. g.  h.  i.	vner, at the proposed site nairperson (or both) will The Driveway placem placement will considintersections.  Minimum surface wide Minimum of 6 feet on Minimum of 6 feet of Driveway should flare surface width of 24 feet Driveway, where it must sides of the driveway Culvert size, or wheth each individual ditch. clearance culvert may determined on a casewidth of 24 feet.  The sight distance from shall be 350 feet in both directing distance will be determed and inspection of the completed and inspection of the completed and inspection of the completed and inspection of the driveway surface to be an adequate driveway trucks can weigh an expection of the driveway permit of the driveway	te, and determine a l issue the permit ient will be determine and include safe that of driveway to a either side of the fif the lot line of an e at the end, where the tet wide. The eets the town road to keep any water are needed, to be do a If a conventional to be required in soft by-case basis by the manifered in soft by-case basis by the ons. On a roadway mined on a case-by y must be in place must be crushed stone, and we crushed stone, and we crushed stone, and we crushed stone, and we crushed base, and we crushed by eit riveway without further than the stone and be signed by eit riveway without further than the stone and the signed by eit riveway without further than the stone and the signed by eit riveway without further than the stone and the signed by eit riveway without further than the stone and the signed by eit	a suitable location with the following inned by the Town ety, closeness to be 12 feet. Surface width, y adjourning prove it meets the town and the from the drivew letermined by the culvert is require me cases. If need the Town employ on a roadway who will be the from the drivew on a roadway who will be the from the drivew on a roadway who will be the from the speed y-case basis. The prior to a building inspect a sphalt or concrete the from the from employ on the from	thy angled away from the road, and to the ray from running on to the town road. Town employee or Chairperson, based on red, a new steel culvert will be used. A low led, the diameter of the culvert will be ree or Chairperson, but having a minimum here the speed limit is greater than 25 mph, weway surface, and 3-1/2 feet off the road d limit is 23-35 mph or less, the sight reger the edges of the town toad. Driveway must tor and must meet all the requirements the.  erial to support the projected traffic, (fire sed. ication. Payable to the Town of Aztalan.	
location.		f fee is related to	time spent by the	e Town employee or Chairperson on site	
Approved	l DV			Date	